

## **List of figures**

|  |    |
|--|----|
| 2.1. Phase space trajectories and the Poincarè section.....  | 11 |
| 2.2. OGY control algorithm.....  | 14 |
| 3.1. Experimental schematic .....  | 24 |
| 3.2. Nozzle construction details.....  | 29 |
| 3.3. Multivariate statistical techniques used to predict the bubbling regime from the period of formation data. .... | 34 |
| 3.4. Real time identification and fault identification.....  | 36 |
| 4.1. Pressure trace in gas inlet line, upstream of the nozzle.....   | 39 |
| 4.2. 'Shoulders' in pressure time series.....  | 41 |
| 4.3. Pressure trace for period-1 bubbling.....   | 43 |
| 4.4. Power spectrum distribution for period-1 showing a single fundamental peak.....                                 | 43 |
| 4.5. Phase space for period-1 bubbling showing a single-loop.....  | 43 |
| 4.6. High speed images of slow bubbling.....   | 44 |
| 4.7. Pressure trace for period-2 bubbling.....   | 46 |
| 4.8. Power spectrum distribution for period-2 showing two fundamental peaks.....                                     | 46 |
| 4.9. Phase space for period-2 bubbling showing two-loops.....  | 46 |
| 4.10. High speed images of period-2 formation of bubbles.....  | 47 |
| 4.11. Pressure trace for period-4 bubbling.....  | 50 |
| 4.12. Power spectrum distribution for period-4 showing three fundamental peaks.....                                  | 50 |

|  |    |
|--|----|
| 4.13. Phase space for period-4 bubbling showing four-loops.....  | 50 |
| 4.14. Pressure trace for chaotic bubbling.....   | 53 |
| 4.15. Power spectrum distribution for chaotic bubbling.....  | 53 |
| 4.16. Chaos in phase space .....   | 53 |
| 4.17. Pressure traces for bubbling with varying applied electrostatic potential, at a constant<br>flow rate of 334 cc/min.....                         | 55 |
| 4.18. Pressure trace for 1mm ID nozzle at 0kV .....  | 57 |
| 4.19. Pressure trace for 1mm ID nozzle at 5kV.....   | 57 |
| 4.20. Pressure trace for 1mm ID nozzle at 7.5kV.....   | 57 |
| 4.21. Period of formation of bubbles against bubble number, with varying applied electrostatic<br>potential at a constant flow rate of 334 cc/min..... | 58 |
| 4.22. Time return maps with an increase in the applied electrostatic potential at a constant<br>flow rate of 334 cc/min.....                           | 60 |
| 4.23. Time return maps with an increase in the flow rate at a constant applied electrostatic<br>potential of 10,000 V. ....                            | 61 |
| 4.24. Time return maps with an increase in the respective control variable .....   | 63 |
| 4.25. Chaotic strange attractor in a 3-d time return map.....  | 64 |
| 4.26. Phase space variations with varying applied electrostatic potential field strength, at<br>constant flow rate of 334 cc/min .....                 | 66 |
| 4.27. Power spectrum variations with varying applied electrostatic potential field strength, at<br>constant flow rate of 334 cc/min.....               | 67 |

|  |    |
|--|----|
| 4.28. Bifurcation with applied electrostatic potential field strength, at constant flow rate of<br>334 cc/min.....                                     | 69 |
| 4.29. Position of a single run with respect to bifurcation with flow-rate and electrostatic<br>potential in tandem.....                                | 69 |
| 4.30. Bifurcation with flow and voltage.....   | 72 |
| 4.31. Bifurcation with flow and voltage against dimensionless axes.....  | 72 |
| 4.32. Bubbling regime plot in terms of the modified Weber number.....  | 73 |
| 4.33. Bubbling regimes in terms of Tsuge's flow rate number versus electric Bond number<br>.....   | 75 |
| 4.34. Frequency mapped as a surface plot against dimensionless flow-rate and voltage.....  | 76 |
| 5.1. Performance of numerical model using partial least squares.....   | 80 |
| 5.2. Neural network performance for identifying the periodicity of bubbling. ....  | 82 |
| 5.3. Period-1 identification with periodicity pattern identifier.....  | 84 |
| 5.4. Period-2 identification with periodicity pattern identifier.....  | 85 |
| 5.5. An drift of 220cc/min in the disturbance (flow-rate), compensated by voltage to track a<br>set point of constant bubbling frequency (0.05s) ..... | 87 |
| 5.6. Negative step change of 235cc/min in disturbance (flow rate) tracked by voltage for a<br>set point of 0.05s. ....                                 | 88 |
| 5.7. Positive step change of 220cc/min in disturbance (flow rate) tracked by voltage for a set<br>point of 0.05s.....                                  | 89 |
| 5.8. Sorting fixed points on the 45° line on the time return map to find a true fixed-point..  | 92 |

|  |     |
|--|-----|
| 5.9. Identifying the stable and unstable manifold directions. ....                             | 93  |
| 5.10. OGY control attempt with electrostatic potential as the single control variable.....     | 98  |
| 5.11. Frequency distribution of zero crossings before control is turned on (region b).....     | 100 |
| 5.12. Frequency distribution of zero crossings after control is turned on (region $c_1$ )..... | 101 |
| 5.13. Frequency distribution of zero crossings after control is turned on (region $c_2$ )..... | 102 |
| 5.14. Frequency distribution of zero crossings after control is turned off (region d).....     | 103 |